



Platform	Model Count	Available Lengths	Beam Width at Gunnel		Bottom Width and Deadrise		Bottom Thickness		Side Thickness		Side Height		Interior Freeboard	Approx WT	Transom Style		Engine Range	Persons	Fuel Tanks
			Standard	Optional	Standard	Optional	Standard	Optional	Standard	Optional	Standard	Optional			Standard	Optional			
Open	1	20' to 26'	96"	102"	72" / 12 deg.	1	72"-90" 5 deg. / 12 deg./18 deg	.190"	.250"	.125"	.160"	30"	36"			Guide Style	-		
Center Console	2	18' to 26'	96"	102"	72" / 12 deg.	2	72"-90" 5 deg. / 12 deg./18 deg	.190"	.250"	.125"	.160"	30"	36"			30" Offshore Bracket	Guide Style or Motorwell		
Hook	3	18' & 20'	96"	-	72" / 12 deg.	3	5 deg.	.190"	.250"	.125"	.160"	30"	-			30" Offshore Bracket	Guide Style or Motorwell		
Navigator	4	18' to 24'	96"	-	72" / 12 deg.	4	5 deg. / 16 deg.	.190"	.250"	.125"	.160"	30" plus 4" Coaming	30" plus ? Coaming			30" Offshore Bracket	Guide Style or Motorwell		
Navigator Sport	5	18' to 4'	96"	-	72" / 12 deg.	5	5 deg. / 16 deg.	.190"	.250"	.125"	.160"	30" plus 4" Coaming	30" plus ? Coaming			30" Offshore Bracket	Guide Style or Motorwell		
Sentinel	6	18' to 26'	102"	-	76" / 16 deg	6	5 deg. / 12 deg.	.190"	.250"	.125"	.160"	36"	36" plus ? Coaming			30" Offshore Bracket	Guide Style or Motorwell		
Sentinel Pro	7	20' to 32'	102"	-	84" / 16 deg w/ reverse chine	7	-	.250"	-	.125"	.160"	36"	36" plus ? Coaming			30" Offshore Bracket	Guide Style or Motorwell		
Sentinel XL	8	22' to 38'	108"	-	90" / 18 deg	8	72"-90" 5 deg. / 12 deg./18 deg	.250"	-	.125"	.160"	33" plus 4" Coaming	33" plus ? Coaming			30" Offshore Bracket	Guide Style or Motorwell		
Voyager	9	22' to 28'	102"	108"	84" / 16 deg w/ reverse chine	9	72"-90" 5 deg. / 12 deg./18 deg	.250"	-	.125"	.160"	36"	36" plus ? Coaming			30" Offshore Bracket	Guide Style or Motorwell		
Explorer	10	22' to 32'	102"	114"	84" / 16 deg w/ reverse chine	10	72"-90" 5 deg. / 12 deg./18 deg	.250"	-	.125"	.160"	36" plus 6" Coaming	36" plus ? Coaming			30" Offshore Bracket	Guide Style or Motorwell		
Baja (maybe different name)	11	26' to 38'	120"	-	102" / 20 deg w/ reverse chine			.250"	-	.160"	-								

541-826-7330
 6241 Crater Lake Hwy
 Central Point, Or 97502